





AAA-PCI-047-K01/K04/P01/P05/P06/P07/P08/P09/P10

NOTES:

1. MATERIAL :
 - 1.1 CARRY TAPE: PS
 - 1.2 COVER TAPE: PET
 - 1.3 SHIPPING CARTON: CORRUGATED FIBER
2. DIMENSION :
 - 2.1 REEL: W=44.5, $\phi A=330$
 - 2.2 SHIPPING CARTON: L=335, W=335, H=300 (INNER)
3. QUANTITY :
 - 3.1 PRIMARY PACKING: 350 PCS/REEL
 - 3.2 SECONDARY PACKING: 6 REELS/CARTON(2100PCS)
4. PEELING RESISTANCE: 20gf~120gf.
5. PEELING SPEED: 300mm/minutes.




GENERAL TOLERANCES UNLESS SPECIFIED		PART NO. SEE TABLE	LOTES			
X± 0.35	X°± 3°					
.XX ± 0.25	X°± 2°	APPROVED BY Barney	TITLE MINI PCI EXPRESS 9.0H 0.8PITCH 52P			
.XXX ± 0.15	.XX°± 1°	CHECKED BY Raymond	DWG NO. AP-AAA-PCI-047			
SIZE	UNITS	DRAWN BY XU		SHEET	SCALE	REV
A4	MM[INCH]			4 / 5	N/A	10



AAA-PCI-047-K02/P07_A/P10_A/P02/P11_A/P12_A

NOTES:

1. MATERIAL :
 - 1.1 CARRY TAPE: PS
 - 1.2 COVER TAPE: PET
 - 1.3 SHIPPING CARTON: CORRUGATED FIBER
2. DIMENSION :
 - 2.1 REEL: W=44.5, ØA=330
 - 2.2 SHIPPING CARTON: L=335, W=335, H=300 (INNER)
3. QUANTITY :
 - 3.1 PRIMARY PACKING: 350 PCS/REEL
 - 3.2 SECONDARY PACKING: 6 REELS/CARTON(2100PCS)
4. PEELING RESISTANCE: 20gf~120gf.
5. PEELING SPEED: 300mm/minutes.



GENERAL TOLERANCES UNLESS SPECIFIED		PART NO. SEE TABLE	LOTES			
X± 0.35	X.°± 3°					
.XX ± 0.25	X.° ± 2°	APPROVED BY Barney	TITLE MINI PCI EXPRESS 9.0H 0.8PITCH 52P			
.XXX ± 0.15	.XX° ± 1°	CHECKED BY Raymond	DWG NO. AP-AAA-PCI-047			
SIZE	UNITS	DRAWN BY XU		SHEET	SCALE	REV
A4	MM[INCH]			5 / 5	N/A	10