



## PCB LAYOUT

- SPECIFICATIONS
- Current Rating: 1A AC, DC
  - Voltage Rating: 125V AC, DC
  - Temperature Range: -25°C~+85°C
  - Contact Resistance: 20mΩ Max
  - Insulation Resistance: 100MΩ Min
  - Withstanding Voltage: 500V AC/minute
  - Material: Wafer Nylon46, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A1251-02A	1.25	4.25
A1251-03A	2.50	5.50
A1251-04A	3.75	6.75
A1251-05A	5.00	8.00
A1251-06A	6.25	9.25
A1251-07A	7.50	10.50
A1251-08A	8.75	11.75
A1251-09A	10.00	13.00
A1251-10A	11.25	14.25
A1251-11A	12.50	15.50
A1251-12A	13.75	16.75
A1251-20A	23.75	26.75

制图 DRAWN		变更内容 DESCRIPTION		日期 DATE		GENERAL TOLERANCE		制 图 DRAWING		料 号 PART NO.		版 本 REV.	
						X.±0.25	X.±2°	审 核 CHECK		2013. 07. 01		品 名 TITLE	
						X.±0.20	X.±1°	核 准 APPROVAL		2013. 07. 03		客户料号 CUST. NO.	
						.XX±0.15	.XX±0.5°			2013. 07. 05		SHEET	
						.XXX±0.10	.XXX±0.5°	单 位 UNITS		MM		比例 SCALE	
										1:1		1/1	

深圳市广德众电子科技有限公司